

Brunswick-Glynn County Joint Water & Sewer Commission 1,500 Gallon Grease Interceptor

MODEL: 110-01520

PRODUCT INFORMATION

1,500 Gallon
Grease Interceptor

Tank = 17,400 # Baffle = 1,300 #
Lid = 5,700 #
DESIGN MAY VARY

SPECIFICATIONS

MEETS ASTM C 1613

RATING: A-16 (H-20), ASSUME
4" MAX EARTH COVER WITH 3'
WATER TABLE BELOW GRADE

CONCRETE: 5,000 PSI @ 28 DAYS

STEEL REINFORCEMENT: MEETS
ASTM A 615, PLACEMENT AS
REQUIRED BY DESIGN


INLET & OUTLET BOOT MEETS
ASTM C 923, ACCEPTS 4" & 6" PVC

BUTYL SEALANT: MEETS ASTM
C 900, USED ON JOINTS

ACCESS OPENING SUITABLE FOR
24" RISER AND/OR RING & COVER
INTERNAL PIPING BY OTHERS
PER MUNICIPAL SPECS

TANK INTERIOR & EXTERIOR
COATED WITH CONSEAL CS-55

CROSSOVERS TO BE 6" PVC



Scale: 1/4" = 1'



**BARTOW
PRECAST**

770.382.4462
sales@bartowprecast.com
WWW.BARTOWPRECAST.COM

DRAWING INFORMATION

Drawn By: CTP

Checked By: _____

Revision: 1

Date: 11/5/2024

APPROVED BY: _____

print: _____

sign: _____

*actual dimensions may vary slightly